

FULL PACKAGING S.R.L.

TYPE: AROUND BUCKET
 MODEL: 11-0300 LB2
 LIDS: P-03LB/1; P-03LB/2
 P-03FB/1

www.full-packaging.it

DIMENSIONS AND WEIGHT

DESCRIPTION	DATA
UPPER DIAMETER (INSIDE)	185,9 mm (b)
UPPER DIAMETER (WITH FLANGE)	200,0 mm (a)
UPPER DIAMETER (WITH HANDLE)	195,5 mm
BOTTOM DIAMETER (EXTERNAL)	168,0 mm (c)
HEIGHT (WITH STANDARD LID)	154,8 mm (h)
HEIGHT (WITH LID FOR VOILING)	160,3 mm
NOMINAL CAPACITY	3.000 ml
TOTAL CAPACITY	3.700 ml
TOTAL USABLE CAPACITY	3.350 ml
CONTAINER WEIGHT	98 g
HANDLE WEIGHT (strap)	2,9 g
HANDLE WEIGHT (short strap)	2,8 g
HANDLE WEIGHT (PP)	6
HANDLE WEIGHT (metal)	18,1 g
WEIGHT TOLLERANCE	+/- 5%
DIMENSION TOLLERANCE	+/- 1mm





PHOTO OF PRODUCT



DECORATION

DESCRIPTION	OFFSET	IML
WIDTH (B) :	565 mm	558,6 mm
HEIGHT (H):	110 mm	138,8 mm



LIDS

DESCRIPTION	DATA
NAME	P-035FB/1
OPTIONAL	YES
WEIGHT	27,5 g
IML	NO
OFFSET	NO



DESCRIPTION	DATA
NAME	P-03LB/1
OPTIONAL	NO
WEIGHT	26 g
IML	YES
OFFSET	NO



DESCRIPTION	DATA
NAME	P-03LB/2
OPTIONAL	NO
WEIGHT	26g
IML	
OFFSET	



RAW MATERIAL/TRANSPORT AND WAREHOUSING

• **Bucket and lids are made of polypropylene (PP)**

• **Warehousing:** In the case of stacking pallets with filled containers put weight

uniformly, using for example proper separators

• **Filling: and closing conditions:** max content temperature during filling 95° C, during stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack.

When temperature decrease to 25-30° containers are characterized by optimal rigidity and mechanical parameters allowing stacking for maximal static load as below.

• **load on the lower container:**

Static (T<23c°). <25 kg

Transparent container < 20 kg

• **Transportation of filled containers :** containers may be stacked to the 66 % of maximal static load.


• **Palletizing of containers:** product with density 1,6g/cm3 according to the customer practice giving consideration to the mentioned earlier values.

• **All materials and dyes used:** to the produce container or lid designed for the food sector are approved for food contact


• **This guarantee** is valid 12 months from date of delivery. During this time, the package should be used. All packages from singles pallet should be used immediately after unpacking.

• **Manufacturer** is not responsible for container deformation because stacking of singles pallets or putting on them an extra load.

PALLETIZATION FILLED CONTAINERS



TOP VIEW



SIDE VIEW
tall

PALLETIZATION AT DELIVERY

1200 unit/pallets
packaging: hood or bag

BASE COLOURS

