
# FULL PACKAGING S.R.L.

www.full-packaging.it

RETTANGULAR BUCKET 11-500 P3 P-05PR/BIS/3

## **DIMENSIONS AND WEIGHT**

DESCRIPTION	DATA
UPPER LENGHT (WITH FLANGE)	287,0mm
UPPER WIDTH (WITH FLANGE)	198,0 mm
BOTTOM LENGHT	252,3mm
BOTTOM WIDTH	165 mm
HEIDGT (WITH STANDARD LID)	150,4 mm
HEIDGT (WITH LID FOR FOILING))	-
NOMINAL CAPACITY	5.000 ml
TOTAL CAPACITY	6.300 ml
TOTAL USABLE CAPACITY	5.800 ml
CONTAINER WEIGHT WITH HANDLE	188 g
WEIGHT TOLLERANCE	+/-5%
DIMENSION TOLLERANCE	+/- 1 mm





TYPE: MODEL:

PHOTO OF PRODUCT

## DECORATION

DESCRIPTION	IML	PARTIAL IML	
WIDTH (B) :	821,6 mm	211,2 mm	
HEIGT (H):	124,5 mm	124,5 mm	B

LID	
DESCRIPTION	DATA
NAME	P-05/PR/BIS3
FOILING	-
WEIGHT	57 g
IML	YES
OFFSET	NO

# RAW MATERAL/TRANPORT AND WAREHOUSING

• Bucket and lids are made of polypropylene (PP)

• Warehousing: In the caseof stacking pallets with filled contaiiners put weight

uniformaly, using for example proper separators

• Filling: and closing conditions: max content temperature during filling 95° C, during stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack.

When temperature decrease to 25-30° containers are characterized by optimal rigidity and mechanical parameters allowing stacking for maximal static load as below.

Ioad on the lower container:

#### Static (T<23c°). <40kg

## PALLETIZAZION FILLED CONTAINERS

4	4	4
		<u></u>
	4	4
4	4	4
	<b>—</b>	-

#### Trasparent containers < 32kg



960 unit/pallets

packaging: hood or bag

1040 unit/pallets

packaging: hood or bag

• Trasportation of filled containers : containers may be stacked to the 66 % of maximal static load.

• Palletizing of containers: product with density 1,6g/cm3

according to the customer pratice giving consideration to the mentioned earler values.

• All materials and dyes used: to the produce container or lid designed for the food sector are pproved for food contact

• **This guarantee** is valod 12 months from date of delivery. During this time, the, the package shoulbe used. All packages from singles pallet shoul be used immediately after un paking.

• **Manufacturer** is not responsible for conatiner deformatrion because stacking of singles pallets or nputting on them an extra load.

