

DIMENSIONS AND WEIGHT

DESCRIPTION	DATA
UPPER DIAMETER (INSIDE)	211,9 mm (B)
UPPER DIAMETER (WITH FLANGE)	225,0 mm (a)
UPPER DIAMETER (WITH HANDLE)	227,3 mm
BOTTOM DIAMETER (EXTERNAL)	194,0 mm (c)
HEIGHT (WITH STANDARD LID)	187,0 mm (h)
HEIGHT (WITH LID FOR FOILING)	194,0 mm (c)
NOMINAL CAPACITY	5.000 ml
TOTAL CAPACITY	5.900 ml
TOTAL USABLE CAPACITY	5.500 ml
CONTAINER WEIGHT WITH HANDLE	130 g
HANDLE WEIGHT (STRAPP)	5,4 g
HANDLE WEIGHT (SHORT STRAPP)	4,6 g
HANDLE WEIGHT (PP)	7,5 g
HANDLE WEIGHT (METAL)	20,3 g
WEIGHT TOLLERANCE	+/- 5%
DIMENSION TOLLERANCE	+/- 1mm





PHOTO OF PRODUCT



DECORATION

DESCRIPTION	OFFSET	IML
WIDHT (B) :	650 mm	643,0 mm
HEIGHT (H):	135 mm	169,5 mm



LIDS

DESCRIPTION	DATA
NOME PRODOTTO	P-05FB/1
OPTIONAL	YES
WEIGHT	40 g
IML	YES
OFFSET	NO



DESCRIPTION	DATI
NOME PRODOTTO	P-05LB/1
OPTIONAL	NO
WEIGHT	35 g
IML	YES
OFFSET	NO



DESCRIPTION	DATA
NOME PRODOTTO	P-05LB/3
OPTIONAL	NO
WEIGHT	35 g
IML	YES
OFFSET	NO



DESCRIPTION	DATA
NOME PRODOTTO	P-05LB/4
OPTIONAL	NO
WEIGHT	32 g
IML	YES
OFFSET	NO



RAW MATERIAL/TRANSPORT AND WAREHOUSING

- Bucket and lids are made of polypropylene (PP)

- Warehousing: In the case of stacking pallets with filled containers put weight uniformly, using for example proper separators

- Filling: and closing conditions: max content temperature during filling 95° C, during stacking content temperature should be lower than 45°C. Put not more than 2 warm containers in the stack.

When temperature decrease to 25-30° containers are characterized by optimal rigidity and mechanical parameters allowing stacking for maximal static load as below.

- load on the lower container:

Static (T<23c°). <30 kg

Transparent container <24 kg

- Transportation of filled containers : containers may be stacked to the 66 % of maximal static load.


- Palletizing of containers: product with density 1,6g/cm3 according to the customer practice giving consideration to the mentioned earlier values.

- All materials and dyes used: to the produce container or lid designed for the food sector are approved for food contact


- This guarantee is valid 12 months from date of delivery. During this time, the package should be used. All packages from single pallet should be used immediately after unpacking.

- Manufacturer is not responsible for container deformation because stacking of single pallets or putting on them an extra load.

PALLETIZATION FILLED CONTAINERS



TOP
VIEW



SIDE
VIEW

PALLETIZATION AT DELIVERY

- 900 unit/pallets
packaging: hood or bag
- 1080 unit/pallets
packaging: hood or bag
- 1134 unit/pallets
packaging: hood or bag

BASE COLOURS

